



Designed for dedicated home cinemas with an acoustically transparent screen

Minimum screen size 16:9 HDTV 130" (2880 x 1620mm)  
Minimum screen size 21:9 scope 120" (2806 x 1184mm)

MX-30 LCR	
Frequency Range	38 Hz - 16 kHz
Power Handling	100 - 700 Watts RMS recommended amplifier power
Sensitivity	98 dB (2.83V / 1m)
Impedance	8 Ohms
Configuration	2-Way
Low Frequency Driver	Single 380mm (15") high stiffness paper cone driver with 75mm (3") voice coil of optimal length for increased linear excursion, wound on high temperature apical former and powerful vented magnet assembly designed for low distortion
High Frequency Driver	A Krix patented designed 90° x 40° short throw horn with 25mm (1") throat, 35mm (1.4") compression driver, ferrite magnet, coated titanium diaphragm and polyimide surround

MX-30 Subwoofer	
Frequency Range	25 Hz - 200 Hz
Power Handling	200 - 1400 Watts RMS recommended amplifier power
Sensitivity	100 dB (2.83V / 1m)
Impedance	8 Ohms
Configuration	Bass reflex, front firing vents
Low Frequency Driver	Single 455mm (18") paper cone driver. 100mm (4") edge-wound copper voice coil, dual spider assembly and vented magnet assembly